

DATASHEET

HOOK tanka sewable X3

patented technology





nominal values in millimeters [mm]

OPENING	lift
MATERIAL* **	NdFeB (36%), PA66GF¹ (30%), PA6² (29%), stainless steel (3%), epoxy (2%)
COLOUR	black
WEIGHT	~ 8 g (weighed)
BREAKING LOAD**	196 N

GENERAL NOTES*

Proceed like stitching zipper. Use a zipper presser foot and stitch length 2-3 mm. (For securing the thread we recommend choosing a position next to the Fidlock part. Otherwise stability could be reduced.)

Elastic rope* can have a diameter of 2-3,5 mm. Rope is not included in order.

ARTICLE NO.	FH-33031-000002(BLK)
PRODUCT	HOOK tanka sewable X3
SCALE	1:1 DIN A4
REVISION / DATE	R01 14.10.2026

* The manufacturer of the end products in which FIDLOCK fasteners are used, bears the responsibility for thoroughly testing that the FIDLOCK products are suitable for the intended applications.
** According to test specification QM-TP-001
*** The nominal mass fractions percentage of the materials are given as rounded whole numbers. Fractions below 0.5% are not given.

Subject to change without notice, errors excepted
Fidlock GmbH | Kirchhorster Straße 39 | 30659 Hannover | Germany